



Standard Druck Drehmomenttabelle

Serie XLCT-VK

| Druck | 2 XLCT | 4 XLCT | 8 XLCT | 14 XLCT | 30 XLCT |
|-------|--------|--------|--------|---------|---------|
| BAR | Nm | Nm | Nm | Nm | Nm |
| 70 | 224 | 441 | 900 | 1559 | 3566 |
| 80 | 257 | 502 | 1029 | 1782 | 4075 |
| 90 | 290 | 564 | 1157 | 2005 | 4585 |
| 100 | 311 | 637 | 1286 | 227 | 5094 |
| 120 | 368 | 763 | 1555 | 2715 | 6114 |
| 140 | 457 | 887 | 1813 | 3163 | 7133 |
| 160 | 526 | 1019 | 2087 | 3628 | 8152 |
| 180 | 593 | 1145 | 2349 | 4076 | 9171 |
| 200 | 661 | 1272 | 2610 | 4523 | 10190 |
| 220 | 727 | 1402 | 2889 | 4989 | 11209 |
| 240 | 793 | 1526 | 3155 | 5436 | 12228 |
| 260 | 862 | 1649 | 3423 | 5879 | 13247 |
| 280 | 929 | 1774 | 3690 | 6326 | 14266 |
| 300 | 997 | 1906 | 3971 | 6791 | 15285 |
| 320 | 1063 | 2032 | 4238 | 7239 | 16304 |
| 340 | 1132 | 2157 | 4506 | 7682 | 17323 |
| 360 | 1198 | 2290 | 4783 | 8151 | 18342 |
| 380 | 1267 | 2416 | 5044 | 8594 | 19361 |
| 400 | 1333 | 2542 | 5308 | 9042 | 20380 |
| 420 | 1403 | 2668 | 5572 | 9490 | 21399 |
| 440 | 1469 | 2797 | 5854 | 9954 | 22418 |
| 460 | 1537 | 2922 | 6122 | 10402 | 23437 |
| 480 | 1603 | 3051 | 6404 | 10868 | 24456 |
| 500 | 1672 | 3177 | 6673 | 11315 | 25475 |
| 520 | 1738 | 3303 | 6945 | 11758 | 26494 |
| 540 | 1804 | 3429 | 7214 | 12205 | 27513 |
| 560 | 1873 | 3559 | 7497 | 12670 | 28532 |
| 580 | 1939 | 3684 | 7765 | 13118 | 29551 |
| 600 | 2008 | 3808 | 8034 | 13565 | 30570 |
| 620 | 2074 | 3938 | 8317 | 14030 | 31589 |
| 640 | 2143 | 4064 | 8583 | 14487 | 32608 |
| 660 | 2209 | 4189 | 8848 | 14921 | 33627 |
| 680 | 2279 | 4315 | 9115 | 15368 | 34646 |
| 700 | 2346 | 4442 | 9381 | 15815 | 35665 |

HYTORC Seis GmbH

Gallscheider Str. 9 A, 56281 Dörth, Tel: 06747 / 59710, Fax: 597129

E-Mail: info@hytorc-seis.de, Internet: www.hytorc-seis.de