



Modell	Antrieb	Leistung in KW	Förderleistung			Gewicht ohne Öl	Abmessungen in mm (AxCxB)	Öl- kühlung
			ND- Stufe in l/min	MD- Stufe in l/min	HD- Stufe in l/min			
MiniJet-230 (50 + 60 Hz)	230V	0,6	4		0,4	14kg	365x250x350	
JetPro 5.3 230V	230V	0,6	5	1,3	0,5	15kg	365x250x350	
JetPro 6.3 400V	400V	0,6	5	1,3	0,5	15kg	365x250x350	
JetPro 9.3 230V	230V	1,5	10	2,2	1,0	25kg	425x250x395	x
VECTOR 230M	230V	1,5	10	2,2	1,0	33kg	500x320x400	x
VECTOR 230 FA1	230V	1,5	10	2,2	1,0	34kg	520x320x400	x
VECTOR 230 FA4	230V	1,5	10	2,2	1,0	36kg	540x320x400	x
VECTOR 400 FA4	400V	1,8	12	3,1	1,4	36kg	540x320x400	x
JetPro 9.3-DWSD	230V	1,5	10	2,2	1,0	29kg	440x260x420	x
JetPro 9.3 Autoflow	230V	1,5	10	2,2	1,0	29kg	460x290x400	x
JetPro 12.3-AD400V 4T	400V	1,8	12	3,1	1,4	26kg	460x290x400	x
Eco2TOUCH™	230V	1,5	7/11		1,1	31kg	500x250x500	x
JetPro 36.3 400V 4T	400V	2x3	34	1,2	4	82kg	650x440x720	x
MiniAir	Luft		6		0,5	16kg	400x250x350	x
JetAir 12.3 4T	Luft		11	2,5	1,1	22kg	440x270x350	x
BigAir 24.3 4T	Luft		22	5	2,2	32kg	470x420x460	x