



Modell		0,5 XLT	0,7 MXT	1 MXT	3 MXT	5 MXT	8 XLT	10 MXT	15 MXT	20 MXT	35 MXT	50 XLT
Drehmoment min	Nm	50	113	184	444	769	1.100	1.585	2.158	2.720	4.842	7.225
Drehmoment max	Nm	509	1.131	1.845	4.446	7.695	11.012	15.857	21.584	27.200	48.425	72.226
Vierkantantrieb	"	1/2	3/4	3/4	1	1-1/2	1-1/2	1-1/2	2-1/2	2-1/2	2-1/2	2-1/2
Drehmoment- genauigkeit	%	±2,5	±2,5	±2,5	±2,5	±2,5	±2,5	±2,5	±2,5	±2,5	±2,5	±2,5
Abmessungen												
B 1	mm	35	42	50	64	80	90,7	100	111	120	145	210
B 2	mm	51	65	72	95	126	130	148	178	200	225	280
H 1	mm	45	57	70	88	115	120	135	150	170	200	170
H 2	mm	80	90	100	120	150	171	175	180	200	240	250
L1	mm	92	100	124	161	194	196	242	268	300	360	390
L2	mm	46	50	60	80	95	105	121	135	144	176	210
R 1	mm	16	21	25	32	40	45	50	55	60	76	76
R 2	mm	65	85	107	135	165	177	210	219	250	300	410
R 3	mm	108	130	160	207	250	274	310	333	380	460	580
Gewicht	Kg	1	1,5	2	4,5	8	9	14	20	25	46	62